


N AND P-CHANNEL POWER MOSFET

GENERAL DESCRIPTION

The SFS0307T4 uses advanced trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. It can be used in a wide variety of applications.

FEATURES

- ◆ N-CHANNEL
 - $V_{DS}=30V, I_D=7.5A$
 - $R_{DS(ON)}=14.0m\Omega(TYP@V_{GS}=10V)$
 - $R_{DS(ON)}=23.5m\Omega(TYP@V_{GS}=4.5V)$
- ◆ P-CHANNEL
 - $V_{DS}=-30V, I_D=-4.7A$
 - $R_{DS(ON)}=32.0m\Omega(TYP@V_{GS}=-10V)$
 - $R_{DS(ON)}=47.0m\Omega(TYP@V_{GS}=-4.5V)$



ORDERING INFORMATION

Part No.	Package	Marking	Material	Packing
SFS0307T4	SOP8-8L	SFS0307T4	Pb Free	Reel

ABSOLUTE MAXIMUM RATINGS (T_J=25°C unless otherwise noted)

Characteristics		Symbol	N-CHANNEL	P-CHANNEL	UNIT
Drain-Source Voltage		V _{DS}	30	-30	V
Gate-Source Voltage		V _{GS}	±20	±20	V
Drain Current	TC=25°C	I _D	7.5	-4.7	A
	TC=70°C		6	-3.3	A
Pulsed Drain Current(note1)		I _{DM}	30	-18	A
Power Dissipation	TC=25°C	P _D	2.8		W
Thermal Characteristics					
Maximum Junction-to-Lead		R _{θJL}	50		°C/W
Junction and Storage Temperature Range		T _J ,T _{stg}	-55 to +150		°C
Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds		TL	300		°C

N-CHANNEL ELECTRICAL CHARACTERISTICS

Characteristics	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Off Characteristics						
Drain -Source Breakdown Voltage	B _{VDS}	V _{GS} =0V, I _D =250μA	30	--	-	V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =30V, V _{GS} =0V	-	--	1	uA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =20V, V _{DS} =0V	-	--	100	nA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =-20V, V _{DS} =0V	-	--	-100	
On Characteristics						
Gate Threshold Voltage	V _{GS(th)}	V _{GS} = V _{DS} , I _D =250μA	1.0	1.6	2.0	V
Static Drain- Source On State Resistance	R _{DS(on)}	V _{GS} =10V, I _D =6A	-	14.0	20	mΩ
		V _{GS} =4.5V, I _D =4A	-	23.5	30	
Dynamic Characteristics						
Input Capacitance	C _{iss}	V _{DS} =15V	-	580	-	pF
Output Capacitance	C _{oss}	V _{GS} =0V	-	58	-	
Reverse Transfer Capacitance	C _{rss}	f=1.0MHZ	-	45	-	
Switching Characteristics						
Turn-on Delay Time	t _{d(on)}	V _{DD} =15V, V _{GS} =10V R _G =3.3Ω, I _D =5A (Note 2.3)	-	5.6	-	ns
Turn-on Rise Time	t _r		-	25	-	
Turn-off Delay Time	t _{d(off)}		-	18.6	-	
Turn-off Fall Time	t _f		-	11.6	-	
Total Gate Charge	Q _g	V _{DS} =15V, I _D =5A	-	16.5	-	nC
Gate-Source Charge	Q _{gs}	V _{GS} =10V	-	2.6	-	
Gate-Drain Charge	Q _{gd}	(Note 2.3)	-	3.2	-	

N-CHANNEL SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS

Characteristics	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Continuous Source Current	I_S	Integral Reverse P-N Junction Diode in the MOSFET	-	-	7.5	A
Pulsed Source Current	I_{SM}		-	-	30	
Diode Forward Voltage	V_{SD}	$I_S=6A, V_{GS}=0V$	-	0.83	1.2	V

P-CHANNEL ELECTRICAL CHARACTERISTICS

Characteristics	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Off Characteristics						
Drain -Source Breakdown Voltage	B_{VDSS}	$V_{GS}=0V, I_D=-250\mu A$	-30	-	-	V
Drain-Source Leakage Current	I_{DSS}	$V_{DS}=-30V, V_{GS}=0V$	-	-	-1	μA
Gate-Source Leakage Current	I_{GSS}	$V_{GS}=20V, V_{DS}=0V$	-	-	100	nA
Gate-Source Leakage Current	I_{GSS}	$V_{GS}=-20V, V_{DS}=0V$	-	-	-100	
On Characteristics						
Gate Threshold Voltage	$V_{GS(th)}$	$V_{GS}=V_{DS}, I_D=-250\mu A$	-1.0	-1.5	-2.5	V
Static Drain- Source On State Resistance	$R_{DS(on)}$	$V_{GS}=-10V, I_D=-3A$	-	32.0	40	$m\Omega$
		$V_{GS}=-4.5V, I_D=-2A$	-	47.0	60	
Dynamic Characteristics						
Input Capacitance	C_{iss}	$V_{DS}=-15V$ $V_{GS}=0V$ $f=1.0MHz$	-	530	-	pF
Output Capacitance	C_{oss}		-	42	-	
Reverse Transfer Capacitance	C_{rss}		-	27	-	
Switching Characteristics						
Turn-on Delay Time	$t_{d(on)}$	$V_{DD}=-15V, V_{GS}=-10V$ $R_G=3.3\Omega, I_D=-3A$ (Note 2.3)	-	8.6	-	ns
Turn-on Rise Time	t_r		-	26	-	
Turn-off Delay Time	$t_{d(off)}$		-	45	-	
Turn-off Fall Time	t_f		-	48	-	
Total Gate Charge	Q_g	$V_{DS}=-15V, I_D=-3A$ $V_{GS}=-10V$ (Note 2.3)	-	17.5	-	nC
Gate-Source Charge	Q_{gs}		-	3.3	-	
Gate-Drain Charge	Q_{gd}		-	5.2	-	

P-CHANNEL SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS

Characteristics	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Continuous Source Current	I_S	Integral Reverse P- N Junction Diode in the MOSFET	-	-	-7.5	A
Pulsed Source Current	I_{SM}		-	-	-30	
Diode Forward Voltage	V_{SD}	$I_S=-3A, V_{GS}=0V$	-	-0.85	-1.2	V

1. Pulse width limited by maximum junction temperature
2. Pulse Test: Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$
3. Essentially independent of operating temperature

N-CHANNEL Typical Performance Characteristics

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-resistance vs. Drain Current




Figure 4. Body Diode Forward Voltage Variation vs. Source Current and Temperature




Figure 5. Capacitance Characteristics





Figure 6. Gate Charge



P-CHANNEL Typical Performance Characteristics

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-resistance vs. Drain Current




Figure 4. Body Diode Forward Voltage Variation vs. Source Current and Temperature




Figure 5. Capacitance Characteristics








Figure 6. Gate Charge




Typical Performance Characteristics




Test Circuit


Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveform



Unclamped Inductive Switching Test Circuit & Waveform



Package Dimensions of SOP8-8L



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.006	0.010
D	4.700	5.100	0.185	0.200
E	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.270 (BSC)		0.050 (BSC)	
L	0.400	1.270	0.016	0.050
theta	0°	8°	0°	8°

Disclaimer:

- ▶ Hi-semicon reserves the right to make changes to the information herein for the improvement of the design and performance without further notice! Customers should obtain the latest relevant information before placing orders and should verify that such information is complete and current.
- ▶ All semiconductor products malfunction or fail with some probability under special conditions. When using Hi-semicon products in system design or complete machine manufacturing, it is the responsibility of the buyer to comply with the safety standards strictly and take essential measures to avoid situations in which a malfunction or failure of such Hi-semicon products could cause loss of body injury or damage to property.
- ▶ Hi-semicon will supply the best possible product for customers!